



Synergy Lights India

Synergize the success



LED

Professional, Industrial, Outdoor,
Commercial & Domestic Lighting Solutions

ABOUT US

Welcome to Synergy, a beacon of excellence in the realm of LED lighting. We have been at the forefront of innovation, driven by a profound commitment to quality and sustainability. At Synergy, we believe in the transformative power of light, and our journey is a testament to the seamless fusion of brilliance and efficiency.

Our foundation rests on a dedication to pushing technological boundaries. Every LED light produced by Synergy is a testament to our pursuit of excellence. Rigorous quality control measures and adherence to industry standards ensure that each product not only meets but exceeds expectations. Our lights are not just sources of illumination; they are expressions of superior craftsmanship, durability, and environmental responsibility.

WHY SYNERGY

Synergy is synonymous with cutting-edge technology. We embrace the future of lighting with a focus on energy efficiency and sustainability. Our LED lights not only brighten spaces but also contribute to a greener planet. By choosing Synergy, you align yourself with a brand that prioritizes eco-conscious design, reducing energy consumption, and minimizing environmental impact.

Explore our diverse range of LED lights, designed to cater to a spectrum of needs. From smart lighting solutions that redefine convenience to customizable fixtures that blend seamlessly with any environment, Synergy offers versatility without compromise. Our product line is a testament to our understanding of evolving lighting needs and our commitment to providing solutions that stand the test of time.

Behind the brilliance of Synergy is a team of industry experts, dedicated to ensuring that every product delivers on our promise of excellence. We don't just illuminate spaces; we illuminate lives. Synergy isn't merely a brand; it's an experience, a commitment to shaping a brighter, greener future. Choose Synergy for unmatched quality, innovative technology, and a journey where synergy transforms light into an extraordinary experience. Join us in redefining illumination, where every moment is brighter and every space, more vibrant.



LED

SYNERGY LED FLOOD LIGHT



Synergy Lights India

Synergize the success

SPREAD GM MODEL



TECH. SPECIFICATION

WATTAGE	30W	50W	100W	150W	200W	250W
RATED VOLTAGE	100V-325V AC					
RATED FREQUENCY	45-55Hz					
POWER FACTOR	>0.97					
SYSTEM POWER EFFICIENCY	89%					
THD	10%					
WORKING HUMIDITY	5% to 95% NON-CONDENSING					
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)					
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)					
CCT	4000K/5700K/6500K					
CRI	Ra >80					
HIGH VOLTAGE CUT OFF	325V					
AMBIENT TEMPERATURE	-10° to 55° C					
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001					

IM MODEL



TECH. SPECIFICATION

WATTAGE	30W	50W	100W	150W	200W	300W
RATED VOLTAGE	100V-325V AC					
RATED FREQUENCY	45-55Hz					
POWER FACTOR	>0.97					
SYSTEM POWER EFFICIENCY	89%					
THD	10%					
WORKING HUMIDITY	5% to 95% NON-CONDENSING					
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)					
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)					
CCT	4000K/5700K/6500K					
CRI	Ra >80					
HIGH VOLTAGE CUT OFF	325V					
AMBIENT TEMPERATURE	-10° to 55° C					
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001					

IM LENS MODEL



TECH. SPECIFICATION

WATTAGE	50W	100W	150W	200W
RATED VOLTAGE	100V-325V AC			
RATED FREQUENCY	45-55Hz			
POWER FACTOR	>0.97			
SYSTEM POWER EFFICIENCY	89%			
THD	10%			
WORKING HUMIDITY	5% to 95% NON-CONDENSING			
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)			
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)			
CCT	4000K/5700K/6500K			
CRI	Ra >80			
HIGH VOLTAGE CUT OFF	325V			
AMBIENT TEMPERATURE	-10° to 55° C			
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001			

LED

SYNERGY LED FLOOD LIGHT



Synergy Lights India

Synergize the success

BACK CHOKE MODEL



TECH. SPECIFICATION

WATTAGE	100W	200W	300W	400W
RATED VOLTAGE	100V-325V AC			
RATED FREQUENCY	45-55Hz			
POWER FACTOR	>0.97			
SYSTEM POWER EFFICIENCY	89%			
THD	10%			
WORKING HUMIDITY	5% to 95% NON-CONDENSING			
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)			
LUMINOUS EFFICIENCY	>120lm/W (AS PER LM-80 REPORT)			
CCT	4000K/5700K/6500K			
CRI	Ra >80			
HIGH VOLTAGE CUT OFF	325V			
AMBIENT TEMPERATURE	-10° to 55° C			
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001			

HI MAST MODEL



TECH. SPECIFICATION

WATTAGE	300W	400W	500W	600W	700W	800W
RATED VOLTAGE	100V-325V AC					
RATED FREQUENCY	45-55Hz					
POWER FACTOR	>0.97					
SYSTEM POWER EFFICIENCY	89%					
THD	10%					
WORKING HUMIDITY	5% to 95% NON-CONDENSING					
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)					
LUMINOUS EFFICIENCY	>120lm/W (AS PER LM-80 REPORT)					
CCT	4000K/5700K/6500K					
CRI	Ra >80					
HIGH VOLTAGE CUT OFF	325V					
AMBIENT TEMPERATURE	-10° to 55° C					
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001					

BEAM MODEL



TECH. SPECIFICATION

WATTAGE	50W	100W	150W	200W	250W
RATED VOLTAGE	100V-325V AC				
RATED FREQUENCY	45-55Hz				
POWER FACTOR	>0.97				
SYSTEM POWER EFFICIENCY	89%				
THD	10%				
WORKING HUMIDITY	5% to 95% NON-CONDENSING				
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)				
LUMINOUS EFFICIENCY	>120lm/W (AS PER LM-80 REPORT)				
CCT	4000K/5700K/6500K				
CRI	Ra >80				
HIGH VOLTAGE CUT OFF	325V				
AMBIENT TEMPERATURE	-10° to 55° C				
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001				

LED

SYNERGY LED FLOOD LIGHT



Synergy Lights India

Synergize the success


BRICK MODEL



TECH. SPECIFICATION

WATTAGE	50W 100W 120W
RATED VOLTAGE	100V-325V AC
RATED FREQUENCY	45-55Hz
POWER FACTOR	>0.97
SYSTEM POWER EFFICIENCY	89%
THD	10%
WORKING HUMIDITY	5% to 95% NON-CONDENSING
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)
CCT	4000K/5700K/6500K
CRI	Ra >80
HIGH VOLTAGE CUT OFF	325V
AMBIENT TEMPERATURE	-10° to 55° C
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001

B-BRICK MODEL



TECH. SPECIFICATION

WATTAGE	100W 200W 300W 400W 600W 800W 1000W
RATED VOLTAGE	100V-325V AC
RATED FREQUENCY	45-55Hz
POWER FACTOR	>0.97
SYSTEM POWER EFFICIENCY	89%
THD	10%
WORKING HUMIDITY	5% to 95% NON-CONDENSING
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)
CCT	4000K/5700K/6500K
CRI	Ra >80
HIGH VOLTAGE CUT OFF	325V
AMBIENT TEMPERATURE	-10° to 55° C
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001

S-BRICK MODEL



TECH. SPECIFICATION

WATTAGE	50W 150W 250W 350W
RATED VOLTAGE	100V-325V AC
RATED FREQUENCY	45-55Hz
POWER FACTOR	>0.97
SYSTEM POWER EFFICIENCY	89%
THD	10%
WORKING HUMIDITY	5% to 95% NON-CONDENSING
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)
CCT	4000K/5700K/6500K
CRI	Ra >80
HIGH VOLTAGE CUT OFF	325V
AMBIENT TEMPERATURE	-10° to 55° C
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001

LED

SYNERGY LED STREET LIGHT



Synergy Lights India

Synergize the success

SLEEK LENS MODEL



TECH. SPECIFICATION

WATTAGE	24W	36W	50W	70W	100W	120W
RATED VOLTAGE	100V-325V AC					
RATED FREQUENCY	45-55Hz					
POWER FACTOR	>0.97					
SYSTEM POWER EFFICIENCY	89%					
THD	10%					
WORKING HUMIDITY	5% to 95% NON-CONDENSING					
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)					
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)					
CCT	4000K/5700K/6500K					
CRI	Ra >80					
HIGH VOLTAGE CUT OFF	325V					
AMBIENT TEMPERATURE	-10° to 55° C					
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001					

ECO MODEL



TECH. SPECIFICATION

WATTAGE	18W	24W	30W	36W	45W	50W	60W
RATED VOLTAGE	100V-325V AC						
RATED FREQUENCY	45-55Hz						
POWER FACTOR	>0.97						
SYSTEM POWER EFFICIENCY	89%						
THD	10%						
WORKING HUMIDITY	5% to 95% NON-CONDENSING						
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)						
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)						
CCT	4000K/5700K/6500K						
CRI	Ra >80						
HIGH VOLTAGE CUT OFF	325V						
AMBIENT TEMPERATURE	-10° to 55° C						
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001						

ECO BIG MODEL



TECH. SPECIFICATION

WATTAGE	70W	100W	120W	150W
RATED VOLTAGE	100V-325V AC			
RATED FREQUENCY	45-55Hz			
POWER FACTOR	>0.97			
SYSTEM POWER EFFICIENCY	89%			
THD	10%			
WORKING HUMIDITY	5% to 95% NON-CONDENSING			
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)			
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)			
CCT	4000K/5700K/6500K			
CRI	Ra >80			
HIGH VOLTAGE CUT OFF	325V			
AMBIENT TEMPERATURE	-10° to 55° C			
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001			

LED

SYNERGY LED INDUSTRIAL LIGHT



Synergy Lights India

Synergize the success

UFO HI BAY MODEL



TECH. SPECIFICATION

WATTAGE	50W	100W	150W	200W	250W
RATED VOLTAGE	100V-325V AC				
RATED FREQUENCY	45-55Hz				
POWER FACTOR	>0.97				
SYSTEM POWER EFFICIENCY	89%				
THD	10%				
WORKING HUMIDITY	5% to 95% NON-CONDENSING				
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)				
LUMINOUS EFFICIENCY	>110Lm/W (AS PER LM-80 REPORT)				
CCT	3000K/4000K/5700K/6500K				
CRI	Ra >80				
HIGH VOLTAGE CUT OFF	325V				
AMBIENT TEMPERATURE	-10° to 55° C				
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001				

FLAME PROOF MODEL



TECH. SPECIFICATION

WATTAGE	90W	120W
RATED VOLTAGE	100V-325V AC	
RATED FREQUENCY	45-55Hz	
POWER FACTOR	>0.97	
SYSTEM POWER EFFICIENCY	89%	
THD	10%	
WORKING HUMIDITY	5% to 95% NON-CONDENSING	
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)	
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)	
CCT	3000K/4000K/5700K/6500K	
CRI	Ra >80	
HIGH VOLTAGE CUT OFF	325V	
AMBIENT TEMPERATURE	-10° to 55° C	
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001	

WELL GLASS MODEL



TECH. SPECIFICATION

WATTAGE	50W	70W	100W	120W
RATED VOLTAGE	100V-325V AC			
RATED FREQUENCY	45-55Hz			
POWER FACTOR	>0.97			
SYSTEM POWER EFFICIENCY	89%			
THD	10%			
WORKING HUMIDITY	5% to 95% NON-CONDENSING			
LED MAKE	OSRAM / BRIDGELUX / SEOUL (2835 9V 1W)			
LUMINOUS EFFICIENCY	>120Lm/W (AS PER LM-80 REPORT)			
CCT	3000K/4000K/5700K/6500K			
CRI	Ra >80			
HIGH VOLTAGE CUT OFF	325V			
AMBIENT TEMPERATURE	-10° to 55° C			
INGRESS PROTECTION	IP 65/IP 66/IP AS PER IS/IEC60529-2001			

LED

SYNERGY LED COMMERCIAL LIGHT



Synergy Lights India

Synergize the success

1X1 RECESS PANEL




18/24W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W / 24W
POWER FACTOR	>0.95PF
RATED FREQUENCY	45-55Hz
SYSTEM EFFICIENCY	>89%
THD	<10%
CRI	80%

COLOURS AVAILABLE
CW, NW, WW,
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



1X1 SURFACE PANEL




18/24W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W / 24W
POWER FACTOR	>0.95PF
RATED FREQUENCY	45-55Hz
SYSTEM EFFICIENCY	>89%
THD	<10%
CRI	80%

COLOURS AVAILABLE
CW, NW, WW,
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



2X2 RECESS PANEL




36/48/60W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	36 / 48 / 60W
POWER FACTOR	>0.95PF
RATED FREQUENCY	45-55Hz
SYSTEM EFFICIENCY	>89%
THD	<10%
CRI	80%

COLOURS AVAILABLE
CW, NW, WW,
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



2X2 SURFACE PANEL




36/48/60W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	36 / 48 / 60W
POWER FACTOR	>0.95PF
RATED FREQUENCY	45-55Hz
SYSTEM EFFICIENCY	>89%
THD	<10%
CRI	80%

COLOURS AVAILABLE
CW, NW, WW,
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



LED

SYNERGY COB SERIES



Synergy Lights India
Synergize the success

COB DOWN LIGHTER


6W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	6W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



COB DOWN LIGHTER


10W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	10W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



COB DOWN LIGHTER


16W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	16W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



COB DOWN LIGHTER


24W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	24W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



COB DOWN LIGHTER


30W / 36W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	30W / 36W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



LED

SYNERGY COB DOWN LIGHTER SERIES



Synergy Lights India

Synergize the success

COB DOWN LIGHTER




7W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	7W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)

Cut Size : 50 mm



COB DOWN LIGHTER




12W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)

Cut Size : 75 mm



COB DOWN LIGHTER




18W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)

Cut Size : 80 mm



COB DOWN LIGHTER

GLOSS/ROSE
GOLD METALLIC
REFLECTOR




12W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)

Cut Size : 75 mm



COB DOWN LIGHTER

GLOSS/ROSE
GOLD METALLIC
REFLECTOR




12W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)

Cut Size : 75 mm



LED

SYNERGY COB SURFACE CYLINDER



Synergy Lights India

Synergize the success

COB SURFACE CYLINDER


7W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	7W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



COB SURFACE CYLINDER


12W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



COB SURFACE CYLINDER


18W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



Synergy Lights India

Synergize the success

LED

SYNERGY COB TRACK & WALL SPOT



Synergy Lights India

Synergize the success

TRACK & WALL SPOT LIGHT


10W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	10W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



TRACK & WALL SPOT LIGHT


20W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	20W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



TRACK & WALL SPOT LIGHT


30W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	30W
POWER FACTOR	>0.98PF
LUMEN EFFICACY	>95 Lm/W
CRI	80% & 90%
COLORS AVAILABLE 2700K° / 3000K° / 4000K° / 5700K° / 6500K°	

DIMENSION (in mm)



Sourced from Internet



LED

SYNERGY INDOOR SERIES



Synergy Lights India

Synergize the success

NIGHT LAMP


0.5W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	0.5W
POWER FACTOR	>0.65PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE	
CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPOT LIGHT


2W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	2W
POWER FACTOR	>0.65PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE	
CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPOT LIGHT


2W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	2W
POWER FACTOR	>0.65PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE	
CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



DEEP DOWNLIGHTER


12W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.97 HPF
LUMEN EFFICACY	>95 Lm/W
CRI	80%
COLOURS AVAILABLE	
CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



DEEP DOWNLIGHTER


18W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE	
CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



LED

SYNERGY LED DEEP LIGHT



Synergy Lights India

Synergize the success

FITON




3W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	3W
POWER FACTOR	>0.65PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)

Cut Size : 50 mm



SELTOS




5W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	5W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)

Cut Size : 64 mm



SHINE




7W

TECH. SPECIFICATION


INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	7W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)

Cut Size : 87 mm



SHINE




12W

TECH. SPECIFICATION


INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)

Cut Size : 50 mm



DUAL COLOR SHINE




8+8W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	8W+8W
POWER FACTOR	>0.90PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)

Cut Size : 50 mm



LED

SYNERGY LED CONCEALED SERIES




Synergy Lights India

Synergize the success

POLO


7W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	7W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



AURO


7W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	0.5W
POWER FACTOR	>0.65PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



HARRIER


7W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	7W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



CRETA


9W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	9W
POWER FACTOR	>0.97PF
HOUSING	ALUMINUM BODY
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



MIRAGE


9W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	9W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLORS AVAILABLE CW+WW=NW, / GREEN+PINK=C/W BLUE+RED=PINK / BLUE+GREEN=ICE BLUE (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



LED

SYNERGY LED SURFACE SERIES



Synergy Lights India

Synergize the success

STRIKER SURFACE

5W




TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	5W
POWER FACTOR	>0.65PF
HOUSING	POLY CARBONATE
CRI	70%

COLOURS AVAILABLE


CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



TRIMLESS DOB

6W




TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	6W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%

COLOURS AVAILABLE

CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



TRIMLESS DOB

12W




TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%

COLOURS AVAILABLE


CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



TRIMLESS DOB

18W




TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%

COLOURS AVAILABLE

CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



LED

SYNERGY LED SURFACE SERIES



Synergy Lights India

Synergize the success

HANDI SURFACE


10W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	10W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SHINE SURFACE


8W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	8W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SHINE SURFACE


15W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	15W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	


DIMENSION (in mm)



BULK HEAD-IP65

FOR
OUTDOOR
USE


10W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	10W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	


DIMENSION (in mm)



BULK HEAD-IP65

FOR
OUTDOOR
USE


20W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	20W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



LED


SYNERGY LED ADJUSTABLE SERIES



Synergy Lights India

Synergize the success

ROUND & SQUARE ADJUSTABLE




12W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



ROUND & SQUARE ADJUSTABLE




24W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	24W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



DUAL COLOR ADJUSTABLE PANEL




12W+12W


TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12+12W
POWER FACTOR	>0.95PF
HOUSING	POLY CARBONATE
CRI	70%
COLORS AVAILABLE CW/WW/NW, GREEN/PINK/CW, BLUE/RED/PINK, BLUE/GREEN/ICE BLUE (OTHER COLORS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



DUAL COLOR ADJUSTABLE PANEL





24W+24W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	24+24W
POWER FACTOR	>0.95PF
HOUSING	POLY CARBONATE
CRI	70%
COLORS AVAILABLE CW/WW/NW, GREEN/PINK/CW, BLUE/RED/PINK, BLUE/GREEN/ICE BLUE (OTHER COLORS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



LED

SYNERGY LED APOLLO SERIES



Synergy Lights India

Synergize the success

APOLLO PANEL


6W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	6W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



APOLLO PANEL


12W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



APOLLO PANEL


18W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



APOLLO SURFACE


12W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



APOLLO SURFACE


18W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



LED

SYNERGY LED SPARK PANEL SERIES



Synergy Lights India

Synergize the success

SPARK PANEL


8W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	8W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPARK PANEL


12W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPARK PANEL


15W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	15W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPARK PANEL


22W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	22W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



LED

SYNERGY LED SPARK SURFACE



Synergy Lights India

Synergize the success

SPARK SURFACE




8W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	8W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPARK SURFACE




15W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	15W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPARK SURFACE




22W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	22W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPARK PANEL 3 IN 1




8W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	8W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLORS AVAILABLE CW+WW=NW, / GREEN+PINK=C/W BLUE+RED=PINK / BLUE+GREEN=ICE BLUE (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SPARK PANEL 3 IN 1




15W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%
COLORS AVAILABLE CW+WW=NW, / GREEN+PINK=C/W BLUE+RED=PINK / BLUE+GREEN=ICE BLUE (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



LED

SYNERGY LED SLIM PANEL SERIES




Synergy Lights India

Synergize the success

SLIM PANEL


6/9W



TECH. SPECIFICATION


INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	6W / 9W
POWER FACTOR	>0.65PF
HOUSING	ALUMINUM
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SLIM PANEL


12/15W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W / 15W
POWER FACTOR	>0.65PF
HOUSING	ALUMINUM
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SLIM PANEL


18/22W



TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W / 22W
POWER FACTOR	>0.65PF
HOUSING	ALUMINUM
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



LED

SYNERGY LED SURFACE PANEL



Synergy Lights India

Synergize the success

SURFACE PANEL




6/9W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	6W / 9W
POWER FACTOR	>0.65PF
HOUSING	ALUMINUM
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SURFACE PANEL




12/15W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	12W / 15W
POWER FACTOR	>0.65PF
HOUSING	ALUMINUM
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



SURFACE PANEL





18/22W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	18W / 22W
POWER FACTOR	>0.65PF
HOUSING	ALUMINUM
CRI	70%
COLOURS AVAILABLE CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER (OTHER COLOURS CAN BE CUSTOMIZED)	

DIMENSION (in mm)



Benefits of Switching to LED Lighting

Long Life-

Long life time stands out as the number one benefit of LED lights. LED lights and diodes have outstanding operational life time expectation of some times up to 100,000 hours.

Energy Efficiency-

LED lights use only 15% of the electricity whereas traditional incandescent light bulbs which operate at 20% energy efficiency only, a 80% of the electricity is lost as heat.

Ecologically Friendly-

LED lights contain no toxic materials and are 100% recyclable, and will help you to reduce your carbon footprint by up to a third. A big step towards a greener future!

Durable Quality-

LEDs are extremely durable and built with sturdy components that are highly rugged and can withstand even the roughest conditions.

Design Flexibility-

LEDs can be combined in any shape to produce highly efficient illumination. Individual LEDs can be dimmed, resulting in a dynamic control of light, color and distribution. Well-designed LED illumination systems can achieve fantastic lighting effects.

Zero UV Emissions-

LED illumination produces little infrared light and close to no UV emissions.

Operational in Extremely Cold or Hot - Temperatures

LED are ideal for operation under cold and low outdoor temperature settings. For fluorescent lamps, low temperatures may affect operation but LED illumination operates well also in cold.

Light Dispersement

LED is designed to focus its light and can be directed to a specific location. Well-designed LED illumination systems are able to deliver light more efficiently to the desired location.

Instant Lighting & Frequent Switching

LED lights brighten up immediately and when powered on, which has great advantages for infrastructure projects and frequent on/off switching does drastically reduce operational life expectancy.

Low & High Voltage

A low-high voltage power supply is sufficient for LED illumination. This makes it easy to use LED lighting also in outdoor areas, and is a big advantage when it comes to using LED technology in Industrial, Commercial and remote or rural areas.



Synergy Lights India

Synergize the success

Synergy Lights India

19/4B, Khatenna Road Lohamandi, Agra-282002
Google Map : 5XQQ+M4 Agra, Uttar Pradesh

✉ synergylightsindia@gmail.com

☎ 8630548607, 8379072138