



Synergy Lights India
Synergize the success

SPARK SURFACE PANEL



SPARK SURFACE




8W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	8W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%

COLOURS AVAILABLE
CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



SPARK SURFACE



15W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	15W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%

COLOURS AVAILABLE
CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)



SPARK SURFACE



22W

TECH. SPECIFICATION

INPUT VOLTAGE	90V - 325V, 50Hz
WATTAGE	22W
POWER FACTOR	>0.97PF
HOUSING	POLY CARBONATE
CRI	80%

COLOURS AVAILABLE
CW, NW, WW, RED, GREEN, BLUE, PINK, AMBER
(OTHER COLOURS CAN BE CUSTOMIZED)

DIMENSION (in mm)

